





RAMAN AMPLIFIED OPTICAL SYSTEM WITH REDUCTION OF FOUR-WAVE MIXING EFFECTS

Patent number: CA2335891
Publication date: 2001-09-03
Inventor: STENTZ ANDREW JOHN (US); REED WILLIAM ALFRED (US); PARK SEO Y (US); LEE ROBERT B (US); HANSEN PER BANG (US)
Applicant: LUCENT TECHNOLOGIES INC (US)
Classification:
- international: **H01S3/30; H04B10/17; H04B10/18; H01S3/30; H04B10/17; H04B10/18; (IPC1-7): H04B10/17; G02F1/39**
- european: H01S3/30F; H04B10/17R; H04B10/18N4
Application number: CA20012335891 20010213
Priority number(s): US20000186793P 20000303; US20010772489 20010130

Also published as:

 EP1130825 (A2)
 US6697558 (B2)
 US2001036347 (A)
 EP1130825 (A3)

Report a data error here

Abstract of CA2335891

A transmission fiber for use in a Raman amplified optical communication system is formed to exhibit certain characteristics that limit modulation instability and four-wave mixing in the amplification region, thus reducing the noise component present in the transmission system. In particular, the group-velocity dispersion (denoted as D and measured in terms of ps/nm-km) is restricted to be either non-positive or greater than +1.5ps/nm-km in the pump wavelength range of interest (a typical pump wavelength range being 1430-1465nm). Preferably, the magnitude of the dispersion is kept below a value of 10 ps/nm-km in the signal wavelength range of interest (e.g., the "C" band or "L" band). Four-wave mixing is reduced by ensuring that the zero-dispersion frequency of the transmission fiber is not centered between the pump frequency and a frequency experiencing Raman gain.

Data supplied from the **esp@cenet** database - Worldwide